



Republika ng Pilipinas
Republic of the Philippines
Kagawaran ng Tanggulang Pambansa
Department of National Defense

DND BIDS AND AWARDS COMMITTEE

Camp General Emilio Aguinaldo, Quezon City

August 07, 2015

SUPPLEMENTAL BID BULLETIN NR. DND-AFP-PAF-SE-2015-01

(Acquisition of Specialized Equipment for the PAF)

This Supplemental Bid Bulletin is being issued to inform prospective bidders of the modifications/amendments and/or additional requirements that shall form part of the bidding documents and to confirm key issues addressed during the Pre-Bid Conference on August 06, 2015, for the Acquisition of Specialized Equipment for the Philippine Air Force.

The amendments attached herein shall be for inclusion in **Section 7: Technical Specification LI No. 10** (after page 75) and **Section VIII Bidding Form 9** (page 124 -blank page) of the Bidding Documents.

Please be guided accordingly.

A handwritten signature in black ink, appearing to read "Ernesto D. Boac", with a stylized flourish at the end.

ASEC ERNESTO D. BOAC

Chairman, DND Bids and Awards Committee

Section VIII. Bidding Forms

L/I	Nomenclature	Specification	Comply/ Not Comply
10	Power Shore set	<p>Includes</p> <ul style="list-style-type: none"> • 2 ea Extension pipe (min length 125 mm/max wt. 1.5 kg) • 2 ea Extension pipe (min length 250 mm/max wt. 2 kg) • 2 ea Extension pipe (min length 500 mm/max wt. 3 kg) • 2 ea Extension pipe (min length 1000 mm/max wt. 5 kg) • 2 ea Mechanical strut (Retracted min length:250mm/min stroke 250 mm/max wt 10kgs) • 2 ea Hydraulic hand pump & hose <ul style="list-style-type: none"> • Working pressure Min : 720 bar • Oil contents: 700cc • Hose length:min 3 mtrs • Weight including hose: max 10 kgs • 2 ea Hydraulic strut w/lock nut (Plunger w/ thread and lock nut) <ul style="list-style-type: none"> • Working pressure: min 720 bar • Force at working pressure : min 100 kN • Retracted length : min 575 mm <ul style="list-style-type: none"> • Stroke : 250 mm • Weight : Max 10 kgs • 2 ea Flat head Support • 2 ea Tilting support on uneven or tilting surfaces • 2 ea Beam support • 2 ea L- support for wide beams • 2 ea head for mutual support • 2 ea V-block support of pipes • 2 ea Multifunctional cross head • 4 ea Base support plate for tensioning belts • 6 ea Tensioning belt minimum length : 4 meters • 2 ea Adjustable hook wrench with mechanical strut • 1 ea 2- way block support for tilting head • 16 ea Anti-roll block • All extension pipe/Mechanical strut/ Hydraulic strut are equipped with snap-lock sys to (dis)connect • Strut should be labelled with indicate load to strength ratio • All extension pipe is equipped w/ reflecting color codes • Carrying case included 	

